

TESCON NAIDECK mono patch

Single-sided nail sealing plaster



Technical data

Substance		
Backing	PE film	
Adhesive	Butyl rubber modified with acrylate	
Release film	silicone-coated PE film	
Attribute	Regulation	Value
Colour	Butyl rubber: grey, film: black	
Thickness	1.1 mm ; 43 mils	
Outdoor exposure	6 months, installed under the counter battens	
Application temperature	-10 °C to 35 °C ; 14 °F to 95 °F	
Temperature resistance	permanent -40 °C to 80 °C ; -40 °F to 176 °F	
Storage	cool and dry	

Application

Use under counter battens for sloped roof structures. TESCO NAIDECK mono patch is suitable for use in creating temporary coverings in accordance with the product data sheets of the Central Association of the German Roofing Trade (ZVDH) for roof underlays. Suitable as an accessory for creating seals during construction work in accordance with SIA 232/1 when combined with roof lining membranes.

- ✓ 300 patches on a roll

Advantages

- ✓ Very good sealing effect: sealing material is pulled into the hole created when a nail or screw is fitted
- ✓ Easy to pre-install on roof underlays or battens
- ✓ Conforms to regulations: satisfies the requirements of ZVDH and of SIA 232/1
- ✓ Material savings: patch is only stuck to the counter batten in the area around the nail/screw
- ✓ Reliable during the construction phase: suitable for temporary coverings during construction work

Substrates

Clean subsurfaces before sticking.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded.

Subsurfaces must be sufficiently dry and stable.

TESCON NAIDECK mono patch can be used on all pro clima exterior membranes, on other underlay and wall lining membranes (e.g. those made of PP and PET) and with MDF panels and wood-fibre underlay panels.

The best results in terms of structural stability are achieved on level, unstructured subsurfaces.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

Pretreatment with TESCO PRIMER is recommended in the case of subsurfaces with insufficient stability.

General conditions

Perforation seals will only be effective on roof lining membranes that have been installed with no folds or creases.

Adhesion can be carried out to the counter batten or to the subsurface that is to be sealed. Press firmly to secure the tape in place.

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

