

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Easy tearing across the tape
- > Highly conformable
- > 14 day clean removal
- > UV resistant
- > Rain repellent
- > Wind resistant
- > Indoor/outdoor
- > Multi-surface
- > Environmentally responsible
- > Does not contain halogens and heavy metals
- > Free of toxic Phthalates
- > REACH conform

TYPICAL APPLICATIONS

- > Exterior Painting
- > Plastering
- > Stucco
- > Hanging Poly-Drop Cloth
- > Protecting

CONSTRUCTION

Overall Grade: Exterior Masking/ Protecting
 Backing: Special Blend of Plastic Compound
 Adhesive: Non-solvent, specially modified UV stable adhesive

COLOR(S)

- Blue White

STANDARD SIZE

Width(s): 2"/48mm; 1.5"/36mm
 Length(s): 45yd/41m

Contact your BDT sales representative for other available sizes and colours.

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	140	my	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 10	N/2,5cm	-
Adhesion to cured paint on drywall	≤ 8	N/2,5cm	-
Tensile Strength	N/A		-
Service Temperature Range	from -5 to +60	°C	-
	from 23 to 140	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed in conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C (70°F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

