

## Data sheet

# MasterMastic PU swelling paste 310 ml

Single-component, solvent-free polyurethane-based swelling paste. MasterMastic PU is a swellable sealing compound for waterproofi ng of concrete construction joints and penetrations. Upon contact with water, the swelling paste expands and seals the joint or penetration reliably and permanently.





### Show product



Product video in further languages



EORI-Nr.: DE 4774124



article number:	010030
article group:	104 - PU-Quellpaste
GTIN:	4251689510403
customs tariff number:	32141010
packing unit:	ct
sales quantity unit:	1 Kt
weight per:	ct = 0.4 kg
material:	polyurethane rubber
colour:	light blue
density:	ca. 1,17 g/ml
texture:	pasty, stable
usage:	approx. 360 ml/m construction joint
	onney 20 100 ml/m well non-stration
a atting time a	approx. 80 - 100 ml/m wall penetration
setting time:	approx. 6 - 7 mm / 24 hrs. at + 20 °C
volume increasement:	approx. 180%
shore (A) hardness:	20 +/-5
test certificate / approvals:	construction joints:
:	Investigation report
	MFPA Leipzig
	P-SAC 02 / 5.1/ 17 -310 (MFPA Leipzig)
	Wall penetrations:
	Investigation report
	MFPA Leipzig
	PB 5.1 / 17-315-1 (MFPA Leipzig)
packaging:	12 pouches (310 ml)/ carton
adheres to:	concrete, steel, stone, rigid PVC, and many more
	!!! Not suitable for polypropylene !!!
application:	for dry and moist substrates
min. shelf life::	best before 12 months after date of production
thermal scope of	+ 5 °C up to + 45 °C
application:	

Seite 2 von 4



waterpressuretightness:	up to max. 5 bar wall penetration
	up to max. 2 bar construction joint
storage:	Store in undamaged and unopened original packaging in a
	dry place out of direct sunlight.
disposal:	Disposal must be made according to official regulations.
	MasterMastic PU contains no solvents and once cured is
	physiologically harmless.



#### **Basis**

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

#### **Indication of law**

The technical information reflects our current knowledge ofMasterMastic PU swelling paste 310 ml. It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

#### The previous data sheets are no longer valid

Print date 08.01.2024, last modified 24.03.2022