

# Data sheet

## MASTERTUBE injection hose (red/yellow)

for sealing construction joints



[Show product](#)



article number:	030050
article group:	300 - Injektionsschlauch
GTIN:	4251689514203
customs tariff number:	39172190
packing unit:	Roll
sales quantity unit:	100 m
weight per:	Roll = 10 kg
material:	PVC plastic hose with a braided sheath made of monofilament mesh
colour:	red / yellow
outside diameter:	approx. 10 mm
inside diameter:	approx. 5 mm
outlet openings:	slotted with valve function
application temperature:	depending on injection agent, approx. + 6°C to +40°C
test certificate / approvals:	General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 16 - 125
pressure water-tightness:	up to max. 2 bar (20 m water column)
suitable for zones with frequently varying water levels:	yes
corresponds to:	Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability) guideline
packaging:	roll of 100 m
storage:	Store in undamaged and unopened original packaging in a dry place out of direct sunlight.
disposal:	Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.

## Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

## Indication of law

The technical information reflects our current knowledge of MASTERTUBE injection hose (red/yellow). It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

## The previous data sheets are no longer valid

Print date 05.01.2024 , last modified 24.03.2022