

Data sheet

MASTERTUBE "YELLOW"

perforated PVC plastic hose.



Show product





Seite 1 von 3



article group: 300 - Injektionsschlauch GTIN: 4251689514227 customs tariff number: 39172190 packing unit: Roll sales quantity unit: 100 m weight per: Roll = 11 kg material: PVC hose colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent, approx. 4 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites, taking into account the local waste disposal regulations.	article number:	030400
customs tariff number: 39172190 packing unit: Roll sales quantity unit: 100 m weight per: Roll = 11 kg material: PVC hose colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent,	article group:	300 - Injektionsschlauch
packing unit: Roll sales quantity unit: 100 m weight per: Roll = 11 kg material: PVC hose colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	GTIN:	4251689514227
sales quantity unit: 100 m weight per: Roll = 11 kg material: PVC hose colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	customs tariff number:	39172190
material: PVC hose colour: yellow outside diameter: inside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) yes requently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	packing unit:	Roll
material: PVC hose colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent,	sales quantity unit:	100 m
colour: yellow outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test	weight per:	Roll = 11 kg
outside diameter: approx. 12 mm inside diameter: approx. 6 mm outlet openings: slotted with valve function application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	material:	PVC hose
inside diameter: outlet openings: approx. 6 mm outlet openings: application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) yes requently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	colour:	yellow
outlet openings: application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. Can be disposed of at municipal waste landfill sites,	outside diameter:	approx. 12 mm
application temperature: depending on injection agent, approx. + 6°C to +40°C test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) yes frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	inside diameter:	approx. 6 mm
test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	outlet openings:	slotted with valve function
test certificate / approvals: General Building Supervisory Test Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. Can be disposed of at municipal waste landfill sites,	application temperature:	depending on injection agent,
Certificate (AbP) MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		approx. + 6°C to +40°C
MFPA Leipzig No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	test certificate / approvals:	General Building Supervisory Test
No.: P-SAC 02 / 5.1 / 119-337 pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		Certificate (AbP)
pressure water-tightness: up to max. 2 bar (20 m water column) suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		MFPA Leipzig
suitable for zones with frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		No.: P-SAC 02 / 5.1 / 119-337
frequently varying water levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	pressure water-tightness:	up to max. 2 bar (20 m water column)
levels: corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m Storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	suitable for zones with	yes
corresponds to: Utility class A for load classes 1 and 2 in accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m Storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	frequently varying water	
accordance with the WU (water impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	levels:	
impermeability)guideline packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	corresponds to:	Utility class A for load classes 1 and 2 in
packaging: 1 roll of 100 m storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		accordance with the WU (water
storage: Store in undamaged and unopened original packaging in a dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,		impermeability)guideline
dry place out of direct sunlight. disposal: Can be disposed of at municipal waste landfill sites,	packaging:	1 roll of 100 m
disposal: Can be disposed of at municipal waste landfill sites,	storage:	Store in undamaged and unopened original packaging in a
		dry place out of direct sunlight.
taking into account the local waste disposal regulations.	disposal:	Can be disposed of at municipal waste landfill sites,
		taking into account the local waste disposal regulations.



Basis

All dimensions and information in this data sheet reflect the results of the laboratory tests that have been carried out. Deviations from the values determined by us under laboratory conditions are possible due to environmental and operating conditions beyond our control. The data in this data sheet only applies for the product delivered by us. The product data corresponds only to the specifications in Germany. Possible country-specific deviations are not taken into account here.

Indication of law

The technical information reflects our current knowledge of MASTERTUBE "YELLOW". It is intended only as information for users. As we do not know the envisaged applications and processing conditions, it is the responsibility of the user to carefully check that the product is suitable for the intended purposes. Due to the different components at the installation site and the working conditions in place there, MASTERTEC cannot provide any guarantee whatsoever for the result of the work. Claims arising from any legal relationship can only be recognised in the event of wilful intent or gross negligence, irrespective of the statements made here or advice provided verbally. In this case the user must prove that he has provided MASTERTEC in writing with all the information required to correctly assess the installation situation in good time. Subject to necessary product specifications or further developments. By providing this information MASTERTEC does not intend to infringe third party rights. The latest data sheet in each case applies. Our corresponding terms and conditions of sale and delivery apply.

The previous data sheets are no longer valid

Print date 08.01.2024, last modified 24.03.2022