

TECHNICAL DATASHEET

MULTI PURPOSE WOOD FILLER

Description & Uses

Cromar AlphaChem Multi-Purpose Wood Filler is specially formulated for all types of repairs to wood including window frames, doors, skirting boards etc. It gives good adhesion and flexibility when set and can be stained, varnished or painted as required. Available in two colours, white and brown.

Directions

Preparation: Ensure surfaces to be filled are clean, dry and dust free. Remove unsound or rotten wood to give a solid base for the repair. Overpaint nails and metal fittings with an oil-based primer.

- Work tube well between fingers before opening.
- Press filler firmly into the repair using an appropriate tool. For deep repairs fill to a maximum thickness of 13mm (½ inch) and allow to set before applying the next layer.
- Fill slightly proud of the surrounding surface and rub down when completely set to give a perfect finish.
- When used outdoors seal the filler with an oil-based paint or varnish. Protect the filled area from rain and water until sealed. Do not use in areas that are permanently wet.



Cleaning

Clean tools with water before filler sets hard.

Storage

Store in cool, dry conditions between +5°C and +25°C. Protect from frost. After use, ensure lid is firmly replaced.

Shelf Life

12 months when stored in original, unopened packaging.

Limitations

- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.

Technical Data

Physical State	Paste
Odour	PVA Type
Viscosity	2900-3200 (Helipath SF/Sp10)
Flash Point	Not applicable
VOC Content	Not applicable

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.