



Fix & Grout Tile Adhesive Technical Data Sheet

Description

Fix & Grout is ideal for fixing tiles to most substrates, including wood and surfaces subject to small movement, and dries super white. Fix & Grout can also be used for tiling areas subject to frequent wetting, such as showers and bathrooms, and is ideal for grouting.

Directions

Preparation:

Ensure all surfaces are clean, sound and free from loose material, grease etc. Prime new plaster/porous surfaces with Bartoline PVA adhesive. Use an oil-based primer to seal new timber.

Application:

As a Tile Adhesive: Apply to surface to be tiled and spread evenly with a notched spatula to a maximum thickness of 3mm. Fix tiles within 20 minutes of applying adhesive and remove excess adhesive with a damp cloth. Allow 24 hours to dry thoroughly before grouting.

As a Tile Grout: Push grout directly into joints using a grout float. Leave for a few minutes to harden and remove excess with a damp cloth or sponge. Use a grout finisher to make joints neat and tidy. Leave to harden overnight then polish with a damp cloth. Protect areas from water until grout has completely dried.

Cleaning & Storage

Replace cap/lid firmly. Clean tools with water before the adhesive/grout sets. Store in cool dry conditions, protecting from frost and direct sunlight.

Health and Safety

See MSDS for full information.

Technical Data

Also see CE Declaration of Performance (DOP)

Measurement	Value	Test Method
Physical State	Thick Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity Tubs	2200 – 2500	Helipath T-F/ speed 10
Viscosity Tubes	2700 - 3000	Helipath T-F/ speed 10
pH Tubs	9.0	
pH Tubes	7.5 – 8.5	

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
330g Tube	52850120	5010789850128	05010789420666	6	236	1416	59	4
500g Tub	52850150	5010789850159	05010789158699	6	176	1056	16	11
1Kg Tub	52850130	5010789850135	05010789366315	6	96	576	12	8
2.5Kg Bucket	52850140	5010789850142	05010789850159	8	27	216	9	3

Customs Tariff Code

3214 1010

Shipping Classification

Non-Hazardous for shipping purposes