



SEALANTS • ADHESIVES • COATINGS

Technical Datasheet BM25

Version February 2024

BM25

Product Description

BM25 is a 1-component, solvent-based, air drying polyacrylate/silane based primer.

Typical Applications

Priming of porous surfaces such as concrete, blockwork, brickwork etc. before the use of BuildMaster silicones and MS/Hybrid polymer sealants.

Technical Properties

Density: 0.95

Skin Formation Time (at 20°C): 60 minutes

Ideal Processing Temperature: +5°C to +30° C

Shelf Life: 9 months

Application

Joint surfaces must be clean, dry, and free from contamination. Apply one coat of BM25 Primer using a clean dry brush and allow it to dry for at least 1 hour. If sealant application is not finished within the working shift, on the following day, apply another coat of BM25 and allow to dry before restarting sealant application.

Cleaning

Clean brushes immediately after use with a suitable solvent based cleaner.

Packaging

500ml cans

Colour: Dries to a clear film.

Safety Precautions & Disposal

Please refer to the information on our Safety Datasheet.

Warranty

All information in this Technical Datasheet is based on our current technical knowledge and experience. As conditions and methods of use and application of our products are beyond our control, we suggest that you test the product before final use. Information on this sheet is not a warranty. The properties and characteristics stated on this sheet are indicative. We reserve the right to alter and change the product according to technical progress and new developments.

BUILDMASTERUK LIMITED

Company Number: 13922165 Vat No: 412859588 sales@buildmasteruk.com

Unit 2, The Old Colliery Yard, Main Road, Morton, Alfreton, Derbyshire DE55 6HL