

## Declaration of Performance

Version: November 2024



LE/DoP-Nr: MS440HighTack-11-24-001

1. Identification code: Hybrid Sealant **BOND MS 440 High Tack**
2. Identification no: 1-Component Hybrid Adhesive
3. Designated use: Joint sealant based on hybrid polymers.  
Sealant for façade elements in interior application, type F
4. Manufacturer: SCIBO BV  
Valeriusstraat 251h  
1075GB Amsterdam
5. Authorized representative: ./.
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1: 2012-12;
8. Notified body: Internal Testing, IFT Rosenheim 0757
9. Important characteristics:

Important characteristic	Performance	harmonized technical specification
Fire behaviour	Class E	<b>EN 15651 – 1: 2012-12</b>
Release of hazardous chemicals to health and/or the environment	Evaluated	
Water- and airtightness		
a) Stability under load	≤ 5 mm	
b) Tensile properties: Elongation at break (23 °C)	≥ 25 %	
c) Volume loss	≤ 45 %	
Durability	Passed (NF)	

10. The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9. Please see the technical datasheets, safety data sheets and our technical documentation.

This declaration of performance is issued under the responsibility of the manufacturer.

Amsterdam, 01.11.2024

Nils Schmitz