



MULTI-PURPOSE SPRAY LUBRICANT

Low Viscosity Lubricating Spray

Technical Data Sheet



INDUSTRIAL ADHESIVES RANGE

Description:

A low viscosity solvent and oil blend giving excellent lubricating properties of engineered parts. Supplied in aerosol cans with a straw for accurate dispensing.

Features & Benefits:

- ◆ *Excellent anti-corrosive properties.*
- ◆ *Deep penetrating.*
- ◆ *De-watering properties.*
- ◆ *Multi-application fluid.*
- ◆ *Protects tools and metals from rusting.*
- ◆ *Aids dismantling of seized or rusted parts.*

Uses

Can be used for a wide range of demanding uses for automotive and general engineering. Suitable for freeing seized fasteners particularly where corrosion is a problem. Also as a general purpose lubricant and cleaner to free tight linkages. Displaces moisture and condensation from material surfaces. Light duty lubricant which can be directed towards hard to access components. Due to its anti-seize formulation it can also be used as a starting aid for damp ignition systems.

Preparation

Ensure surfaces are clean, dry and grease and oil free.

Application

Attach the straw to the nozzle and aim at the component, keeping the can upright. For seized parts allow to penetrate from all angles for some seconds and progressively loosen adding more lubricant as the threads free.

For stiff linkages remove old grease or dirt and direct the jet onto the linkage until free of old build up, activate linkage to allow full penetration. Reseal with fresh grease for heavy duty applications. To displace moisture wipe away excess then spray a light coat across all surfaces. Do not spray at hot surfaces or live electrical systems.

Size

400ml aerosol tin.

Colour

Clear liquid.

Shelf Life

Minimum 12 months from date of manufacture when stored in original, unopened cans. See bottom of can for batch/manufacture reference.

Storage Conditions

Store below +50°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Observe the label precautions. MULTI-PURPOSE SPRAY LUBRICANT must be stored in accordance with the flammable liquid storage regulations. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce canister. Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

Health & Safety

Extremely flammable aerosol.

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Colourless liquid
Flammability	Extremely flammable aerosol
Flash Point	-40°C
Boiling Point	+140°C
pH	N/A
Solubility in Water	Insoluble
Commodity Code	3403198000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BIMP400	Clear	400ml	5060021361363	K470-V0XP-C00X-98SG



Part of the Bond It Glues & Adhesives Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 5: 08/05/24
Supersedes V4 10/10/22



Certificate Number 6152
ISO 9001
ISO 14001
ISO 45001

bond it

An **ASTRAL** Limited Company